

Filed for intro on 02/02/95  
House Bill \_\_\_\_\_  
By \_\_\_\_\_

Senate No. SB0539  
By Wallace

AN ACT to amend Tennessee Code Annotated, Title 55, Chapter 7, relative to the transportation of overdimensional articles or commodities.

BE IT ENACTED BY THE GENERAL ASSEMBLY OF THE STATE OF TENNESSEE:

SECTION 1. Tennessee Code Annotated, Title 55, Chapter 7, Part 2, is amended by adding the following language as a new, appropriately designated section:

Section 55-7-2\_\_.

(a) Notwithstanding any other provision of law, rule or regulation to the contrary, the commissioner of transportation shall prescribe by orders of general application, rules and regulations for the issuance and/or renewal of special permits for a period of one (1) year, for the transportation of manufactured roof trusses that are in excess of the dimensions set forth in Sections 55-7-201 and 55-7-202.

(b) Such special permits for overdimensional manufactured roof trusses shall be subject to the following conditions:

(1) For movements not exceeding ten (10) feet wide, no escort vehicle, special signs, lights and or markings shall be required.

(2) Movements over ten (10) feet wide but not exceeding twelve (12) feet wide:

(A) No escort vehicle shall be required to accompany the movement on the Interstate highway system, four (4) lane highways, or two (2) lane highways with a minimum pavement (roadway surface) width of twenty-four (24) feet.

(B) One (1) escort vehicle shall be required to precede the movement where the minimum pavement (roadway surface) width is less than twenty-four (24) feet.

(C) A flagperson shall be required at all bridge structures where the roadway width is less than twenty (20) feet.

(D) The front and rear of the movement shall be appropriately signed and marked.

(E) Escort vehicles shall be appropriately marked.

(3) Movements over twelve (12) feet wide but not exceeding fourteen (14) feet wide:

(A) Front and rear escort vehicles shall be required on all two (2) lane highways. Front escort vehicles shall not be required on Interstate highways or four (4) lane highways. Front and rear escort vehicles shall be required on Interstate highways where two (2) lanes are traveled.

(B) Towing vehicles and escort vehicles shall be so equipped as to be in radio communication at all times during movement.

(C) The front and rear of the movement shall be appropriately signed and marked.

(D) Escort vehicles shall be appropriately marked.

(E) Towing vehicles for fourteen foot (14') wide movements shall be at least fourteen feet six inches (14'6") in length.

(c) Compliance with the conditions specified in subdivisions (2)(D), (2)(E), (3)(C) and (3)(D) of this section shall be in accordance with the rules and regulations of the department of transportation relative to overweight and overdimensional movements on Tennessee highways (Chapter 1680-2-2).

(d) Any conflict in the requirements relative to overlength movements, as established by statute, rule or regulation, and the requirements for overwidth movements of manufactured roof trusses established in this section shall be resolved by applying the more stringent requirements.

(e) The commissioner of transportation shall prescribe an annual fee for a special permit to transport overdimensional manufactured roof trusses. Such annual fee shall be predicated upon the department's costs in enforcing the provisions of this section.

SECTION 2. This act shall take effect July 1, 1995, the public welfare requiring it.